

Volume-06|Issue-09|September|Year-2026 ISSN: 3049-2343

International Journal of Academic and Industrial Research Innovations(IJAIRI)

Research Paper Title :Satellite–6G and Geospatial Sensor Fusion for Quantum-Secure Carbon Measurement, Environmental Digital Twins and Global Climate Intelligence

¹Murali Krishna Pasupuleti

¹Research Director

¹National Education Services,

¹New Delhi,India

¹mkrishnap2050@gmail.com

Abstract:

Climate mitigation increasingly depends on carbon measurements that are spatially explicit, temporally frequent, auditable and resilient to cyber-physical manipulation. Existing satellite, terrestrial sensing, digital-twin and mobile-network solutions remain fragmented, while emerging 6G and low-Earth-orbit infrastructures create both an opportunity for continuous environmental intelligence and a new security surface. This paper proposes a model-based architecture that integrates Earth-observation satellites, terrestrial geospatial sensors, 6G/LEO connectivity, uncertainty-aware multimodal fusion, environmental digital twins and quantum-resilient trust controls for carbon measurement, reporting and verification (MRV). The methodological contribution is the Satellite–6G Quantum-Secure Environmental Digital Twin Intelligence (S6Q-EDTI) framework. It combines matrix state estimation, dynamic digital-twin updating, constrained multi-objective optimization, Bayesian uncertainty propagation and a risk-adjusted climate-intelligence score. The literature supplied for the study supports the feasibility of GIS-based environmental digital twins, secure 5G/6G twins, LEO routing, sensor-fusion architectures, quantum/post-quantum communications and Earth-observation analytics (Rusnák et al. 2026; Khan, Qureshi & Abd Malek 2026; He et al. 2026; Miao et al. 2026). An illustrative 0–10 numerical example yields a composite system score of 8.55/10 under assumed weights, while explicitly avoiding claims of empirical validation. The paper further develops an invention-oriented architecture and draft claim concepts centered on cryptographically verifiable provenance, cross-layer fusion, adaptive routing and uncertainty-bounded carbon estimates. The proposed approach provides a coherent foundation for scalable carbon MRV, environmental digital twins and planetary-scale climate decision intelligence, subject to future field validation, standards alignment and jurisdiction-specific legal review.

Keywords: Satellite–6G integration; geospatial sensor fusion; carbon MRV; environmental digital twin; climate intelligence; low-Earth-orbit networks; post-quantum cryptography; quantum-secure communications; Earth observation; Bayesian data fusion; uncertainty quantification; provenance; edge intelligence; climate-risk analytics; digital-twin orchestration.

Copyright:

© 2026 by Murali Krishna Pasupuleti.

1. Introduction

Reliable climate intelligence requires the conversion of heterogeneous observations into decision-grade estimates of emissions, removals, ecosystem condition and risk. Satellite systems provide broad spatial coverage, while ground and mobile sensors offer local temporal detail. Yet these modalities differ in resolution, sampling cadence, calibration stability and vulnerability to missing or adversarial data. The research problem is therefore not simply to collect more measurements, but to fuse them into a traceable environmental state representation whose uncertainty and provenance can be inspected throughout the inference chain.

Recent work on GIS-based digital twins demonstrates the growing role of geospatially grounded virtual representations for environmental monitoring and climate-change analysis (Rusnák et al. 2026). Sensor-fusion research similarly shows that distributed sensing can be combined with autonomous reasoning and digital-twin processes, although much of the literature remains domain-specific (Alvim et al. 2026). In parallel, 6G-oriented digital twins and LEO networking are moving toward adaptive optimization, AI-native control and low-latency connectivity (Yurt, Ulus & Tunc 2025; Xie et al. 2026; Sallent et al. 2024).

The security dimension is equally important. Carbon and environmental measurements can influence financial claims, regulatory compliance, infrastructure operations and international reporting. Consequently, measurement integrity cannot be separated from communications security, device identity, provenance and long-term cryptographic resilience. Quantum-resilient threat modelling for 6G corridors, post-quantum/quantum fusion protocols for LEO links and quantum key-negotiation architectures illustrate the emerging technical basis for such protection (Hafeez, Abro & Mustafa 2025; Khan, Qureshi & Abd Malek 2026; Dong, Huang & Zhang 2026).

This paper therefore treats climate intelligence as a cyber-physical estimation problem spanning observation, communications, fusion, digital-twin state evolution and decision support. The contribution is not a claim of field-tested performance; rather, it is a rigorous system formulation that links the major layers mathematically and operationally. The framework is designed for future empirical testing using real satellite, atmospheric, ecosystem, network and security telemetry.

Research Problem

Existing environmental measurement systems generally separate Earth observation, ground sensing, network transport, cybersecurity and digital-twin inference. This separation creates three technical failure modes: heterogeneous observations cannot be reconciled with consistent uncertainty; data provenance may be lost or unverifiable as measurements traverse multi-operator terrestrial and non-terrestrial networks; and carbon-MRV outputs can become stale or non-auditable when network latency, missing data or sensor faults are not integrated into the state-estimation logic.

1.1 Research Questions

RQ1. How can satellite Earth-observation and terrestrial geospatial sensors be fused through 6G/LEO networks while preserving spatial-temporal consistency and quantified uncertainty?

RQ2. How can post-quantum and quantum-ready security controls protect environmental data provenance, routing and carbon-MRV outputs across edge, satellite and cloud layers?

RQ3. What mathematical representation can connect observation quality, network performance, fusion confidence, digital-twin fidelity and carbon-estimation reliability in a unified model?

RQ4. How can environmental digital twins assimilate multimodal observations continuously without overstating precision when data are sparse, delayed or contradictory?

RQ5. What multi-objective optimization criteria are appropriate for balancing accuracy, latency, energy use, security strength and carbon-MRV confidence?

RQ6. Which architecture elements appear potentially differentiating for an invention-oriented implementation when compared with the supplied prior-art references?

1.2 Research Objectives

O1. To design an integrated Satellite–6G–geospatial architecture for secure environmental sensing and carbon MRV.

O2. To formulate mathematical models for sensor fusion, dynamic digital-twin updating, risk adjustment and constrained optimization.

O3. To construct an illustrative numerical scoring model that demonstrates transparent aggregation without presenting assumed values as empirical evidence.

O4. To identify implementation variables, validation metrics and uncertainty controls suitable for later field deployment.

O5. To synthesize the supplied literature into a clear research-gap and prior-art differentiation analysis.

O6. To develop a patent-oriented invention framework with system, method and dependent-claim concepts for later professional legal drafting.

2. Literature Review

Environmental digital twins are increasingly positioned as dynamic geospatial representations rather than static dashboards. Rusnák et al. (2026) explicitly connect GIS-based digital twins with environmental monitoring and climate change. This provides a conceptual base for spatially registered state estimation, but the reference does not itself establish the full Satellite–6G–quantum-secure carbon-MRV chain proposed here.

Distributed sensor fusion and autonomous reasoning provide a second pillar. Alvim et al. (2026) present a sensor-based multi-agent ecosystem coupling sensor fusion, digital twins and autonomous-agent reasoning. Although the application domain differs, the architecture supports the broader principle that heterogeneous physical observations can feed an adaptive digital representation and decision layer. Pan et al. (2025) further emphasize hierarchical multi-level attention for sensor-fault tolerance in digital twins, reinforcing the need to make fusion robust to defective channels rather than assuming clean inputs.

For communications, 6G digital-twin research highlights optimization, intent coordination and secure predictive control. Yurt, Ulusu and Tunc (2025) study intent fusion and conflict resolution in 6G networks through digital twins; Sallent et al. (2024) frame optimization as a service exploiting network digital twins; and He et al. (2026) connect secure 5G/6G AI-driven digital twins with real-time monitoring and predictive control. Xie et al. (2026) address hierarchical routing for 6G LEO satellite networks, which is directly relevant when environmental observations traverse non-terrestrial segments.

Security references point toward a hybrid future in which post-quantum and quantum mechanisms coexist. Khan, Qureshi and Abd Malek (2026) describe an adaptive multipath quantum/post-quantum fusion protocol for LEO satellite communications.

Hafeez, Abro and Mustafa (2025) examine quantum-resilient threat modelling for RIS-assisted integrated sensing and communication in 6G UAV corridors. Dong, Huang and Zhang (2026) provide an example of AI combined with quantum key negotiation in a secure-communications architecture. Together, these sources motivate a security plane that is not a bolt-on encryption layer but an integral control variable in routing, fusion and provenance.

The geospatial-intelligence layer also requires machine-readable spatial context. Ech-Chadi et al. (2026) propose a cognitive spatial foundation for agentic AI in urban digital twins. Xiang et al. (2026) show deep-learning-aided fusion under GNSS-denied conditions, illustrating how robust state inference can persist when a globally available positioning modality becomes unreliable. For Earth-observation intelligence, Miao et al. (2026) use Earth-observation data and multivariable machine learning to assess climate-driven lag and cumulative vegetation effects, demonstrating the analytical value of global remote-sensing time series.

The supplied corpus additionally includes Pasupuleti (2026a), which focuses specifically on satellite-based carbon MRV using remote sensing and atmospheric inference, and Pasupuleti (2026b), which considers Earth-system foundation models integrating satellite, oceanic and land-surface intelligence. These works provide topic-specific context for linking measurement, inference and climate intelligence while the present paper adds a 6G/LEO, quantum-secure, digital-twin and cross-layer optimization emphasis.

Prior-Art Differentiation Matrix

Supplied reference	Relevant disclosed direction	Potential distinction of proposed combination
Rusnák et al. 2026	GIS-based environmental digital twins	Adds 6G/LEO transport, quantum-secure provenance and carbon-MRV confidence coupling
Alvim et al. 2026	Sensor fusion + digital twins + agents	Adds geospatial carbon measurement, non-terrestrial networking and

		cryptographic trust plane
Yurt, Ulusu & Tunc 2025	Intent fusion in 6G digital twins	Applies cross-layer orchestration to environmental sensing and verifiable MRV
Hafeez, Abro & Mustafa 2025	Quantum-resilient security for 6G UAV/ISAC	Couples security state to sensor-fusion acceptance and carbon confidence
Khan, Qureshi & Abd Malek 2026	Quantum/PQ fusion for LEO communications	Extends secure transport into provenance-bound environmental state assimilation
He et al. 2026	Secure 5G/6G AI digital twins	Adds carbon MRV, satellite/ground geospatial fusion and explicit uncertainty outputs
Xie et al. 2026	Adaptive routing in 6G LEO networks	Adds data-value and trust-aware routing tied to digital-twin assimilation
Pan et al. 2025	Fault-tolerant sensor fusion in digital twins	Adds quantum-secure provenance, LEO/6G orchestration and carbon audit output

Independent System

1. A computer-implemented environmental intelligence system comprising: a plurality of satellite and terrestrial sensing nodes configured to generate geospatially and temporally referenced environmental observations; a terrestrial and non-terrestrial communications fabric including at least one 6G network segment and at least one satellite network segment; a cryptographic trust subsystem configured to associate the observations with integrity, identity, calibration or provenance evidence using a quantum-resilient cryptographic mechanism; a multimodal fusion processor configured to generate an environmental state estimate and an uncertainty measure

from the observations; an environmental digital-twin engine configured to update a versioned digital representation according to the state estimate, the uncertainty measure and freshness or integrity criteria; and a carbon measurement processor configured to generate a carbon measurement, reporting or verification output together with a machine-verifiable confidence and provenance descriptor.

Independent Method

2. A computer-implemented method comprising: acquiring heterogeneous Earth-observation and terrestrial environmental measurements; assigning geospatial-temporal metadata and source-specific uncertainty to the measurements; selecting one or more terrestrial or non-terrestrial communication paths according to latency, reliability, energy and security criteria; cryptographically binding provenance or calibration evidence to the measurements using a quantum-resilient mechanism; fusing the measurements to estimate an environmental state and associated uncertainty; conditionally assimilating the estimated state into an environmental digital twin based on integrity, freshness and confidence thresholds; estimating a carbon quantity or flux from the updated digital twin; and outputting the carbon estimate with an uncertainty descriptor and verifiable data-lineage record.

Dependent-System


3. The system of claim 1 wherein the satellite observations include at least two of optical, SAR, hyperspectral, thermal or atmospheric measurements.
4. The system wherein the cryptographic trust subsystem supports crypto-agile switching among classical, post-quantum and hybrid key-establishment modes.
5. The system wherein routing cost includes a data-value term derived from the expected reduction in digital-twin state uncertainty.
6. The system wherein an observation failing a cryptographic-attestation or calibration-validity condition is quarantined or down-weighted during fusion.
7. The system wherein the fusion processor generates a covariance, credible interval or conformal uncertainty bound for the carbon estimate.
8. The system wherein the environmental digital twin preserves versioned state transitions and cryptographic hashes for audit reconstruction.

9. The system wherein the carbon-MRV output includes spatial support, temporal support, model version, sensor provenance and an integrity status.
10. The method wherein edge nodes perform preliminary anomaly detection and compress or prioritize observations before satellite/6G transmission.
11. The method wherein the communications path is reconfigured in response to a predicted latency violation, security-risk increase or link degradation.
12. The method wherein contradictory observations are resolved by source reliability, uncertainty, calibration age and spatial-temporal consistency scores.

2.1 Conceptual Framework

The conceptual model assumes that climate-intelligence quality is produced by a chain of interdependent capabilities rather than by any single sensor or model. Observation quality influences fusion accuracy; 6G/LEO connectivity determines whether observations arrive within a useful assimilation window; security and provenance controls determine whether inputs and outputs can be trusted; fusion quality affects the state estimate; state-estimation quality drives environmental digital-twin fidelity; and twin fidelity constrains the confidence of carbon MRV and climate-risk outputs. The architecture therefore treats uncertainty, latency and cryptographic trust as co-determinants of decision quality.

Figure 2. Conceptual Causal Chain for Secure Carbon and Climate Intelligence



Uncertainty propagates across the chain; provenance and calibration constrain error accumulation.

Figure 2. Conceptual causal chain linking observations, 6G connectivity, security, fusion, digital-twin fidelity, carbon MRV and climate intelligence.

2.2 Research Gap

Theoretical gap. The supplied literature contains strong component-level research, but no single cited work integrates satellite Earth observation, terrestrial sensor fusion, 6G/LEO transport, quantum-resilient provenance, environmental digital twins and carbon-MRV confidence within one mathematical system model.

Methodological gap. Existing digital-twin and sensor-fusion studies frequently optimize domain-specific performance, whereas environmental MRV requires simultaneous treatment of geospatial registration, asynchronous observations, uncertainty propagation, cryptographic integrity and network constraints.

Empirical gap. The available source set does not provide a shared benchmark dataset spanning satellite imagery, atmospheric measurements, terrestrial carbon sensors, 6G/LEO telemetry and cryptographic events. Hence this paper necessarily remains model-based and illustrative.

Sectoral and policy gap. Carbon claims can have regulatory and financial consequences, but communications reliability and provenance are often separated from the MRV model. A cross-layer architecture is needed to expose confidence bounds, provenance evidence and operational assumptions to auditors and decision-makers.

3. Methodology

This paper proposes a model-based analytical framework and uses illustrative numerical scoring for demonstration; empirical validation requires real-world data collection.

The research design is systems-analytic and constructive. It synthesizes the supplied literature into a layered reference architecture; defines state, observation, security and network variables; develops matrix, dynamic, probabilistic and optimization equations; and performs an illustrative normalized scoring exercise. A future empirical program would sample geographically diverse carbon-monitoring sites and combine satellite scenes, atmospheric products, terrestrial sensors, meteorological measurements, land-cover attributes, network telemetry and cryptographic audit logs. Validation would

include cross-sensor calibration, temporal holdouts, spatial transfer tests, ablation analysis, uncertainty calibration, latency stress tests and adversarial-integrity tests.

Figure 1. Proposed Satellite-6G Quantum-Secure Environmental Intelligence Architecture




Figure 1. Proposed Satellite-6G quantum-secure environmental intelligence architecture.

Novel Architecture / Method

The proposed architecture uses a cross-layer trust-and-fusion controller that jointly selects sensor observations, communications paths, cryptographic protection and digital-twin assimilation actions according to information value, latency, uncertainty, energy and residual security risk. Each observation is associated with geospatial-temporal metadata, calibration state and cryptographic provenance. A fusion engine computes both the environmental state estimate and its uncertainty; the environmental digital twin updates only when freshness, integrity and confidence thresholds are satisfied. Carbon outputs are emitted with a machine-verifiable provenance chain and confidence descriptor.

Implementation

Satellite and airborne modalities may include optical, SAR, hyperspectral, thermal, atmospheric and GNSS-derived products; terrestrial modalities may include gas concentration, flux, weather, soil, hydrology and ecosystem sensors.

6G/LEO connectivity is abstracted as a graph whose edges carry latency, bandwidth, reliability, energy and cryptographic-cost attributes. The controller can reroute observations when trust or freshness thresholds are violated.

The trust plane may support post-quantum key establishment, hybrid classical/PQ mechanisms, QKD-ready interfaces, hardware-rooted attestation, signed calibration records and append-only provenance receipts.

The fusion plane may use covariance-weighted estimation, attention-based fusion, Bayesian filtering or graph/tensor models, provided that per-source uncertainty is retained.

The digital twin maintains a versioned state and can reject, down-weight or quarantine observations that fail anomaly, integrity, calibration or temporal-consistency checks.

Carbon-MRV outputs include estimated quantity, spatial-temporal support, uncertainty interval, data lineage, model version and integrity status.

3.1 Mathematical Framework

Let the latent environmental state at location g and time t be $x(g,t)$, containing carbon flux, atmospheric concentration, vegetation condition, soil state, meteorology and relevant nuisance variables. Let $y_k(g,t)$ denote the observation from modality k , with modality-specific operator H_k and noise ε_k .

$$y_k(g,t) = H_k x(g,t) + \varepsilon_k(g,t), \varepsilon_k \sim N(0, R_k) \quad (1)$$

A confidence-weighted multimodal fusion estimate can be represented as:

$$\hat{x}_t = (\sum_k H_k^T R_k^{-1} H_k + \Lambda)^{-1} (\sum_k H_k^T R_k^{-1} y_{k,t} + \Lambda \bar{x}_t) \quad (2)$$

where Λ regularizes the solution toward a prior state $\bar{x}_t$. In matrix state-space form:

$$x_{t+1} = A_t x_t + B_t u_t + w_t; y_t = H_t x_t + v_t \quad (3)$$

The environmental digital twin evolves dynamically through assimilated observations, process forcing and model corrections:

$$dx/dt = F(x(t), u(t), \theta) + Gz(t) + \zeta(t) \quad (4)$$

where $z(t)$ is a data-assimilation correction derived from current observations. A practical objective is multi-criteria rather than accuracy-only:

$$\min_{\pi} J(\pi) = \alpha E_{MRV} + \beta L + \gamma E_{net} + \delta R_{sec} + \eta U \text{ subject to } C_{bw}, C_{energy}, C_{latency}, C_{security} \quad (5)$$

Here E_{MRV} is carbon-estimation error, L is end-to-end latency, E_{net} is communications/compute energy, R_{sec} is residual cyber/cryptographic risk and U is uncertainty penalty. The policy π controls routing, sampling, fusion and compute placement.

A Bayesian carbon estimate for a reporting unit can be written:

$$p(C|Y, P) \propto p(Y|C, P)p(C|P) \quad (6)$$

where C is net carbon quantity, Y is the multimodal observation set and P is provenance/calibration metadata. This formulation makes audit information part of the conditioning set rather than an external document.

A risk-adjusted climate-intelligence score is defined as:

$$CI^* = [\sum_i w_i s_i] \times T \times (1 - U_n) \times (1 - R_n) \quad (7)$$

where s_i are normalized capability scores, w_i are weights summing to one, T is a trust/provenance factor in $[0, 1]$, U_n is normalized uncertainty and R_n is residual normalized security risk.

3.1.1 Symbol Definitions

Symbol	Definition
$x(g, t)$	Latent geospatial environmental state vector at location g and time t
y_k	Observation from sensor or Earth-observation modality k
H_k	Observation operator mapping state to modality k
R_k	Observation-noise covariance
Λ	Regularization/prior-information matrix
A_t, B_t	State-transition and control matrices
u_t	Exogenous forcing or control input
$w_t, v_t, \xi(t)$	Process, observation and dynamic-model

	noise
π	Joint routing/sampling/fusion/compute policy
E_MRV	Carbon measurement/reporting/verification error term
L	End-to-end latency
E_net	Network and computational energy use
R_sec	Residual security/cryptographic risk
U	Uncertainty penalty
C	Carbon quantity or flux of interest
Y	Combined observations
P	Provenance and calibration metadata
CI*	Risk-adjusted climate-intelligence score
T	Trust/provenance factor

3.2 Numerical Model for Better Insight

The following numbers are illustrative and normalized from 0 to 10; they are not measurements from a field deployment. Assume component scores $S = \{8.6, 8.1, 8.8, 9.0, 8.3, 8.5\}$ for satellite coverage, 6G connectivity, sensor fusion, quantum-security readiness, twin fidelity and MRV confidence. Let weights be $\{0.16, 0.14, 0.20, 0.18, 0.15, 0.17\}$.

$$\text{Base score} = 0.16(8.6) + 0.14(8.1) + 0.20(8.8) + 0.18(9.0) + 0.15(8.3) + 0.17(8.5) = 8.58 \quad (8)$$

If the trust/provenance factor $T=0.98$, normalized uncertainty $U_n=0.06$ and residual security risk $R_n=0.03$, a strict multiplicative risk-adjusted score would be $7.90/10$. For a capability-oriented dashboard that reports system readiness prior to risk discounting, the weighted capability score remains $8.58/10$. To avoid conflating these two meanings, this paper reports $8.58/10$ as the illustrative capability score and $7.90/10$ as the illustrative risk-adjusted operational score.




Figure 3. Illustrative normalized component scores used in the numerical demonstration.




Figure 4. Illustrative uncertainty reduction across calibration, fusion, digital-twin assimilation and carbon-MRV output.

3.3 Data and Variables

Variable	Definition	Measurement	Expected effect	Relevance
SC	Satellite coverage and revisit adequacy	0–10 or physical revisit interval	+	Determines broad spatial observability
TQ	Terrestrial sensor quality	0–10; calibration error	+	Improves local temporal detail
NC	6G/LEO connectivity quality	0–10; latency/loss	+	Controls timely data assimilation
SF	Multimodal fusion quality	0–10; RMSE/calibration	+	Reduces modality-specific error
QS	Quantum/PQ security readiness	0–10; compliance and key metrics	+	Protects links and long-term confidentiality/integrity
PV	Provenance verifiability	0–10; verified event ratio	+	Supports auditability and tamper detection
DT	Digital-twin fidelity	0–10; state error	+	Represents physical system accurately
UN	Normalized uncertainty	0–1	–	Reduces confidence of MRV and decisions
SR	Residual security risk	0–1	–	Discounts operational trust
CM	Carbon-MRV confidence	0–10; CI width/coverage	+	Primary measurement-quality output
CI	Climate-intelligence usefulness	0–10	+	Decision-level outcome

3.4 Proposed Model / Framework

The proposed model is named the Satellite–6G Quantum-Secure Environmental Digital Twin Intelligence framework (S6Q-EDTI). It consists of six coupled planes: observation, transport, trust, fusion, twin and decision. Its compact system equation is:

$$S6Q-EDTI_t = \Phi(Y_{sat,t}, Y_{ground,t}, N_6G,t, Q_{sec,t}, P_t; \theta) \rightarrow \hat{x}_t, \hat{C}_t, U_t, CI_t \quad (9)$$

The mapping Φ is implemented as an uncertainty-aware fusion and assimilation pipeline. The outputs are the estimated environmental state $\hat{x}_t$, carbon estimate $\hat{C}_t$, uncertainty U_t and climate-intelligence output CI_t . The architecture is intentionally modular so that individual sensing modalities, cryptographic suites or digital-twin models can be replaced without invalidating the system-level structure.

4. Results and Analysis

Because no empirical dataset was supplied, the results are analytical and illustrative. The architecture analysis indicates that the strongest system design is not the one that maximizes a single sensing metric, but the one that prevents weak links from dominating end-to-end trust. High-resolution satellite observations do not produce audit-grade carbon estimates if provenance is uncertain; secure links do not compensate for poorly calibrated sensors; and a high-fidelity digital twin becomes stale if network latency prevents timely assimilation.

Scenario	Fusion	Security	Latency	Twin fidelity	MRV confidence	Interpretation
A: Integrated S6Q-EDTI	8.8	9.0	8.1	8.3	8.5	Balanced cross-layer performance
B: Strong sensing, weak security	9.0	5.0	8.0	8.4	6.8	Good estimates but limited audit trust
C: Secure but poorly connected	8.2	9.2	5.5	6.9	7.0	Trustworthy data arrive too slowly for dynamic use

D: Fast network, weak fusion	6.2	8.4	9.0	6.4	6.5	Low latency cannot correct inconsistent modalities
------------------------------	-----	-----	-----	-----	-----	--

Scenario comparison shows why cross-layer co-design matters. In the integrated case, no individual component is maximized, yet the absence of a severe bottleneck produces the highest overall MRV confidence. This supports the use of constrained multi-objective optimization rather than isolated subsystem tuning. The analysis also implies that uncertainty should be reported as an operational output, not hidden inside model diagnostics.

The supplied literature is consistent with these design choices. Secure 5G/6G digital twins support real-time monitoring and predictive control (He et al. 2026); LEO routing work supports adaptive handling of non-terrestrial traffic (Xie et al. 2026); sensor-fault-tolerant digital-twin fusion motivates robustness to unreliable streams (Pan et al. 2025); and Earth-observation machine learning demonstrates the value of temporally extensive geospatial datasets for climate inference (Miao et al. 2026).

4.1 Discussion

Theoretical contribution. S6Q-EDTI reframes environmental intelligence as a joint estimation-and-trust system. Rather than treating cybersecurity, telecommunications and environmental modelling as separate domains, the framework places them in the same objective function and uncertainty budget.

Practical relevance. A deployment could support carbon-project monitoring, national inventory augmentation, methane/CO₂ anomaly investigation, ecosystem restoration verification, climate-resilient infrastructure monitoring and transboundary environmental intelligence. Different use cases would select different sensors but retain the same architectural planes.

Policy implications. Decision-makers should distinguish raw measurement accuracy from verifiable measurement confidence. A carbon estimate with a narrow statistical interval but weak provenance may be less decision-useful than a slightly less precise estimate with traceable calibration, cryptographic attestation and reproducible fusion logic.

Industry implications. Telecommunications operators, satellite providers, sensor manufacturers, cloud platforms and carbon-MRV providers could interoperate through explicit data-quality, provenance and uncertainty contracts. The 6G network may act as an adaptive orchestration substrate rather than only as a transport pipe, consistent with digital-twin optimization research (Sallent et al. 2024).

Technological implications. Quantum/post-quantum readiness should be treated as cryptographic agility. The supplied references support hybrid and quantum-resilient approaches, but the specific cryptographic suite for a real deployment must be selected according to current standards, device constraints and threat models rather than assumed generically.

Ethical considerations. Planetary sensing can create surveillance, sovereignty, fairness and data-governance concerns. Carbon and climate analytics should therefore apply proportionality, access controls, transparent uncertainty reporting, purpose limitation and documented governance for cross-border geospatial data.

5. Conclusion

This paper develops an integrated research framework for Satellite–6G and geospatial sensor fusion in quantum-secure carbon measurement, environmental digital twins and global climate intelligence. The S6Q-EDTI architecture connects heterogeneous observation systems, 6G/LEO communications, provenance and cryptographic trust, uncertainty-aware fusion, dynamic environmental twins and carbon-MRV decision outputs. The mathematical formulation combines state-space modelling, covariance-weighted fusion, dynamic systems, Bayesian inference and constrained multi-objective optimization. The illustrative numerical analysis demonstrates how capability and risk-adjusted scores should be separated, thereby preventing assumed values from being misrepresented as empirical evidence. The primary contribution is architectural coherence: the framework treats accuracy, latency, uncertainty and trust as coupled properties of a single environmental intelligence system. Future work should move from conceptual synthesis to real-world multisite validation, interoperability testing and standards-aligned security evaluation.

5.1 Limitations

The study has five main limitations. First, no raw empirical dataset was supplied, so numerical values are illustrative. Second, measurement models for carbon differ across forests, soils, oceans, cities and industrial sources, limiting universal parameterization. Third, the framework simplifies real 6G/LEO scheduling, propagation and energy constraints. Fourth, cryptographic performance and regulatory acceptability will evolve as standards and implementations mature. Fifth, the prior-art discussion is a research-oriented comparison of the supplied references and is not a legal patentability or freedom-to-operate opinion.

5.2 Future Research Directions

1. Field trials coupling satellite observations with calibrated terrestrial flux, atmospheric and ecosystem sensors over multiple biomes.
2. Physics-informed and graph-based environmental digital twins with explicit conservation constraints and uncertainty propagation.
3. Adaptive 6G/LEO routing that co-optimizes latency, energy, data value and cryptographic overhead for environmental workloads.
4. Standards-aligned post-quantum cryptographic agility, hardware attestation and tamper-evident provenance for long-lived climate records.
5. Federated and privacy-preserving geospatial learning for cross-border climate intelligence without unrestricted raw-data pooling.
6. Causal attribution methods that distinguish climate-driven changes from land-use, sensor drift and observation-selection effects.
7. Auditable carbon-MRV confidence models that combine statistical uncertainty, provenance strength, spatial representativeness and model risk.
8. Open benchmark datasets and digital-twin challenge environments spanning Earth observation, ground sensing, network telemetry and security events.

References

- Alvim, P, F. da Silva, J, Amorim, V, Lazaroni, P, Silva, M & Oliveira, R 2026, 'A Sensor-Based Multi-Agent Ecosystem for Biomechanical Analysis: A Framework for Sensor Fusion, Digital Twins, and Autonomous Agent Reasoning', Proceedings of the 28th International Conference on Enterprise Information Systems, pp. 1182–1189, <http://dx.doi.org/10.5220/0014967600004018>.
- Dong, J, Huang, K & Zhang, X 2026, 'Construction and Application Research of Quantum Secure Communication Model for Intelligent Education—A Fusion Architecture Based on Artificial Intelligence and Quantum Key Negotiation', Proceedings of the 2026 International Conference on Artificial Intelligence and Digital Services, pp. 120–125, <http://dx.doi.org/10.1145/3803686.3803706>.
- Ech-Chadi, M, Ech-Chadi, S, Echchadi, Y & Aghoutane, B 2026, 'The Cognitive Spatial Foundation: Geospatial Intelligence for Agentic AI in Urban Digital Twins', 2026 International Conference on Circuit, Systems and Communication, pp. 1–5, <http://dx.doi.org/10.1109/iccsc71566.2026.11649979>.
- Hafeez, S, Abro, GEM & Mustafa, H 2025, 'Quantum-Resilient Threat Modelling for Secure RIS-Assisted ISAC in 6G UAV Corridors', 2025 International Conference on Computational Intelligence, Security, and Artificial Intelligence, pp. 1–6, <http://dx.doi.org/10.1109/intellisecai66368.2025.11473060>.
- He, X, Zhang, Y, Jiang, Y, Jia, C, Chen, D & Zhong, Y 2026, 'Real-Time Monitoring and Predictive Control of Offshore Engineering via Secure 5G/6G AI-Driven Digital Twins', IEEE Communications Standards Magazine, pp. 1–10, <http://dx.doi.org/10.1109/mcomstd.2026.3659612>.
- Khan, SM, Wasim Qureshi, A & Abd Malek, MF 2026, 'Adaptive Multipath Quantum Post Quantum Fusion Protocol for Low Earth Orbit Satellite Communication', 2026 International Conference on Secure Information Systems and Technologies, pp. 45–52, <http://dx.doi.org/10.1109/icsist70215.2026.11705751>.
- Miao, Z, Li, C, Su, T & Wu, Y 2026, 'Global assessment of climate-driven lag and cumulative effects on vegetation using Earth Observation data and multivariable machine learning models', International Journal of Applied Earth Observation and Geoinformation, vol. 152, p. 105403, <http://dx.doi.org/10.1016/j.jag.2026.105403>.

- Pan, L, Li, H, Li, X, Bi, D, Peng, L & Xie, Y 2025, ‘Hierarchical Architecture Based on Parallel Fusion of Multi-level Attention Neural Networks for Sensor Fault Tolerance in Digital Twins’, <http://dx.doi.org/10.2139/ssrn.5768103>.
- Pasupuleti, MK 2026a, ‘Satellite-Based Carbon MRV: Remote Sensing and Atmospheric Inference for Verifiable Carbon Removal’, *International Journal of Academic and Industrial Research Innovations (IJAIRI)*, vol. 06, no. 02, National Education Services, pp. 142–165, <http://dx.doi.org/10.62311/nesx/rp-f82026>.
- Pasupuleti, MK 2026b, ‘Earth System Foundation Models for Predicting Extreme Climate Events Through Integrated Satellite, Oceanic, and Land-Surface Intelligence’, *International Journal of Academic and Industrial Research Innovations (IJAIRI)*, vol. 06, no. 03, National Education Services, pp. 29–59, <http://dx.doi.org/10.62311/nesx/rp2-30032026>.
- Rusnák, M, Tomáš, G, Lukáš, M & Afzali, H 2026, ‘GIS-Based Digital Twins for Environmental Monitoring and Climate Change’, in *Digital Twin Technology in Geospatial Science: Trends, Applications and Challenges*, pp. 115–134, http://dx.doi.org/10.1007/978-3-032-20311-3_7.
- Sallent, O, Martínez-Caro, J-M, Baliosian, J, Diez, L, Contreras, LM, Pérez-Romero, J, Gorricho, JL, Richart, M, Agüero, R, Serrat, J, Pavón-Mariño, P & Vilà, I 2024, ‘An Optimization-as-a-Service platform for 6G exploiting network digital twins’, in *Digital Twins for 6G: Fundamental Theory, Technology and Applications*, pp. 237–268, http://dx.doi.org/10.1049/pbte109e_ch9.
- Stamou, A, Friedman, N, Landi, F, Chiachío, J, Koutantos, N, Tzouvali, M, Stamoulis, GD, Stankovski, V & Trujillo, JA 2026, ‘Structural Health Monitoring and Earthquake/Climate Proofing by Means of AI Sensor Fusion, Digital Twins and Smart Oracles’, *IOCUS 2026*, p. 14, <http://dx.doi.org/10.3390/eesp2026045014>.
- Xiang, Z, Wang, Q, Nie, X & Zhou, J 2026, ‘Deep learning-aided Laser Doppler Velocimeter-Inertial Measurement Unit Fusion for Robust Vehicle Localization in Global Navigation Satellite Systems-denied environments’, *Engineering Applications of Artificial Intelligence*, vol. 165, p. 113425, <http://dx.doi.org/10.1016/j.engappai.2025.113425>.
- Xie, D, Li, L, Chen, W, He, X, Ruan, W, Bian, J, Yang, Q, Mao, X & Zhu, Y 2026, ‘AHCR: An Adaptive Hierarchical Clustering Routing Algorithm for 6G LEO Satellite Networks’, 2026 Global 6G Conference, pp. 1–8, <http://dx.doi.org/10.1109/global6g69473.2026.11566717>.

Yurt, S, Ulusu, BN & Tunc, C 2025, 'Intent Fusion: Resolving Agent Conflicts Through Large Language Models and Digital Twins in 6G Networks', 2025 IEEE Globecom Workshops, pp. 550–555, <http://dx.doi.org/10.1109/gcwkshps68340.2025.11591105>.